New Off-Road Compression-Ignition Engines



Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR ENGINE FAMILY DISPLACEM (liters)		DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)		
2003	3CEXL0359AAA	5.9	Diesel	8000		
SPECIAL FEATURES & EMISSION CONTROL SYSTEMS			TYPICAL EQUIPMENT APPLICATION			
Direct Diesel Injection, Turbocharger			Crane, Loader, Tractor, Dozer, Pump, Compressor			

The engine models and codes are attached.

The following are the exhaust certification standards (STD), or family emission limit(s) (FEL) as applicable, and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED POWER	EMISSION STANDARD		EXHAUST (g/kw-hr)					OPACITY (%)		
CLASS	CATEGORY		HC	NOx	NMHC+NOx	co	PM	ACCEL	LUG	PEAK
37 ≤ KW < 75	Tier 1	STD	N/A	9.2	N/A	N/A	N/A	20	15	50
		FEL	N/A	9.0	N/A	N/A	N/A	N/A	N/A	N/A
		CERT		5.7				3	2	5

BE IT FURTHER RESOLVED: That the family emission limit(s) (FEL) is an emission level declared by the manufacturer for use in any averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2423 and 2427.

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

777 day of November 2002.

Allen Lyons, Chief

Mobile Source Operations Division

Engine Model Summary Form Aਸਤੇਕਮਵਿਲਾ ਿਤ੍ਹ (ਕੀ (

9910-200-J-17

Manufacturer: Cummins Inc.

Engine category: Nonroad Over 50 Hp

EPA Engine Family 3CEXL0359AAA

Mfr Family Name: A402

Process Code: New Submission

	4
Q	·
8.Fuel Rate: 9.Emission Control bs/hr)@peak torque Device Per SAE J1930	1 2
ĞΠ	aaa L
9.Emission Control evice Per SAE J193	DDI,TG
ssic Per	
(E) (E)	
9.E	
ď	
ji ≱	
R Sa	30.6 29.2 29.2
8.Fuel Rate: hr)@peak tor	ଳ ନିର୍ଦ୍ଧ
유 (출	
<u>\$</u>	
쪽	
7.Fuel Rate: n/stroke@pe torque	
uel Ra troke@ torque	62 63
F.E.	
7.Fuel Rate: mm/stroke@peak torque	
ε	
Σ	900
H (8	50.0
6.Torque @ RPM (SEA Gross)	267@1700 313@1500 325@1400
9.₹	200
ري (ي	8 6 8
6	
ᇁᅎ	
g & E	
8,0,8	37.9 39.6 36
5.Fuel Rate; s/hr) @ peak or diesels ont	ကောက် ၂၂ 🔭
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	
€ਂ≈	
C.	
Ϋ́	
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)	
4.Fuel Rate: stroke @ pea or diesel only	# X X X
die G	47 47 49
4.F stro	
ا ا	
E	
_	97@2200 99@2200 1 99@2000
3.BHP@RPM (SAE Gross)	2200
@ (<u> </u>
품취	97@22C 99@200 99@200
8. S.	666
<u> </u>	
Š	
- 2	B5.9-C B5.9-C
Ĕ.	19 19 19
, E	шша
2.6	
æ	g 9 144
Ř	12 g g g
) ө	J 52
<u>:</u>	
1.Engine Code 2.Engine Model	2071;FR90203 2071;FR91026 2071;FR91026
7	888